

DESCRIPTION

Route Accounting Sales Dot Impact Mobile Printer with Bluetooth communication.

DEVICE COMPATIBILITY

All Buetooth 1.1 compliant devices

PHYSICAL CHARACTERISTICS

- Policarbonate shock-resistant case
- Removable Top Cover for easy ribbon replacement and paper loading

Height: 130 mm (5.12") **Width:** 357 mm (14.05") **Depth:** 298 mm (11.73")

Weight: 4.3 Kg (9.5 lbs.) including paper and batteries

COMMUNICATION

- Bluetooth 1.1
- Service RS-232 (workboard maintenance)

OPTIONS

• GPS SIRF III

PRINTER SPECIFICATIONS

- Dot Matrix 9 pins
- Sprocket tractor feed
- 23/47/62/76 ch/line software selectable
- Bidirectional high speed printing 2.3 lines per second
- 18 lines per second feed speed
- Up to 4 plies multiple copy printing
- Line length from 20 to 60 characters
- Manual/automatic paper forwarding
- Paper Runout warning
- reliable 5 million line mechanism life
- 100 million character printhead life

PAPER

Width: 114mm to 127mm (4.5" to 5")

Length: 279mm (11") max

• 1 to 4 ply fan fold, carbonless NCR paper with adhesive tacking on

• 100 sheet (4 ply) capacity

RIBBON

Black: 3,000,000 characters **Purple:** 5,000,000 characters

FUNCTIONS

- Programmable energy saving system
- Line Feed, Feed, Reset buttons
- Battery discharge/recharge button
- Low battery warning
- Charger and paper status

POWER SUPPLY

- Internal 12 Vdc 2100mAh 25Wh NiMh rechargeable battery pack
- 12Vdc and 24Vdc vehicle power supply, internal step-up DC-DC converter (10-30Vdc)
- External 220V mains power adapter

BATTERY CHARGE LIFE

• 9,000 lines with 2100mAh battery

ENVIRONMENT

Operating: 0°C to 50°C (32°F to 122°F) **Storage:** -25°C to 70°C (-13°F to 158°F) **Rel. Humidity:** up to 80% @ 40°C

REGULATORY APPROVALS

CE Mark

