

MP9000TZ

MOBILE WORKBOARD PRINTER



DESCRIPTION

Route Accounting Sales Mobile Workboard composed of 4" width Zebra RW420 Thermal Direct Zebra Printer and Motorola MC909x-S/B communication and charge holder.

DEVICE COMPATIBILITY

- Motorola/Symbol MC909x-S e MC909x-B
- Zebra RW420 with/without Bluetooth

PHYSICAL CHARACTERISTICS

- Polycarbonate shock-resistant case
- Removable Top Cover for easy ribbon replacement and paper loading

Height: 130 mm (5.12")

Width: 357 mm (14.05")

Depth: 298 mm (11.73")

Weight: 3.2 Kg (7 lbs.) with RW420, 2.3 Kg (5 lbs) without printer

COMMUNICATION

- MC9090 ↔ printer: RS-232 and Bluetooth (order RW420 with Bluetooth option)
- Service RS-232 (workboard maintenance)

OPTIONS

- GPS SIRF III

PRINTER SPECIFICATIONS

- DirectThermal 203dpi 8 dots/mm
- Prints direct thermal tags or receipt paper, synthetic thermal media
- Print Width:** 102mm (4")
- Print Width:** 76.2mm/s (3"/s) max
- Memory:** 8MB flash, 16MB DRAM
- Impact-modified polycarbonate with abrasion-resistant rubber overmould
- Self-centring media holders
- Manual/automatic paper forwarding

FONTS AND GRAPHICS

- 25 fonts, 1 smooth-scalable
- Supports downloadable bitmapped and scalable fonts, user-defined fonts and graphics
- 18 1D linear barcodes, 6 2D Barcodes

PAPER

Width: 50mm to 104mm (2" to 4.12")

Length: 13mm (0.5") to continuous

Label Roll ID: 19mm (0.75") or 34.9mm (1.375")

Label Roll OD: 57mm (2.25") max

Roll Length: 26m (80') approx. max

FUNCTIONS

- Programmable energy saving system
- Line Feed, Feed, Reset buttons
- Battery discharge/recharge button
- Low battery warning
- Charger and paper status

POWER SUPPLY

- 7.4V 4000mAh 30Wh Li-Ion rechargeable battery pack (RW420)
- 12Vdc and 24Vdc vehicle power supply, internal step-up DC-DC converter (10-30Vdc)
- External 220V mains power adapter

BATTERY CHARGE LIFE

- 210m (690') at 20% black density

ENVIRONMENT

Operating: 0°C to 50°C (32°F to 122°F)

Storage: -25°C to 65°C (-13°F to 149°F)

Relative Humidity: 10% to 80% non condensing @ 40°C

REGULATORY APPROVALS

- CE Mark